PRODUCT DATA SHEET



ErgoTec© Art no:ADF-874





Art no:	ADF-874
Size:	6-11
Materials:	Nylon/lycra, nitrile
Packaging:	12/144
Standard:	EN420, EN388:2016
Category:	II

CE CATEGORY: II

EN388:2016 EN420 i

Ē

4121X



Properties

Seamless knitted glove sewn in nylon/lycra and coated in micro foamed nitrile in the palm and over the fingertips. The glove provides excellent grip and can be used for all types of precision work. The gloves are silicone free, solvent free and leave no fingerprints.

Material information

The glove is knitted with a 13 Gauge machine which means 13 stitches per inch. The thread is in nylon/ lycra and coated in micro foamed nitrile in the palm and over the fingertips

formula so called Micro Foam. This technique is 100% water based.

How to read the pictogram:

puncture resistance extended cut resistance impact protection (optional)

Technical facts: Intermediate design (category II) EN388:2016 For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum abcdef score for each level are; abrasion 4, cut resistance 5, tear resist- ance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection abrasion resistance (optional test) P if approved. Evaluate the importance of each of the properties and cut resistance how it applies to you as a user. tear resistance

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se